

DATASHEET - ALL THERMOSTATIC ACID DILUTION EQUIPMENT

When considering equipment to dilute highly corrosive solutions such as concentrated Sulphuric Acid consideration has to be given to:-

- The corrosion resistance of the materials of construction
- The ability of the equipment to control the heat of dilution
- The control of the system to reduce manual intervention

The Chem Resist All Thermoplastic Acid dilution units address corrosion resistance by employing only thermoplastics such as Polypropylene and PVDF.

The dilution vessels, heat exchangers, pumps and pipework are manufactured entirely from these well proven corrosion resistant plastics. The unique internally mounted all thermoplastic heat exchanger in the Chem Resist units eliminates the transfer of hot corrosive liquids in external pipework and allows a compact design to be achieved.



Please note: This data is subject to change without prior notice.

PLC DILUTION CONTROL

The complete PLC control of the dilution process monitors solution temperature and density to allow safe, automatic achievement of the required dilutions with no manual intervention. The Batch dilution units are available in a range of models with capacities from 1m³/hr to 5m³/hr generally as the table below.

For larger volumes Continuous dilution units are available utilising the same thermoplastic heat exchanger technology and PLC control.

Chem Resist Dilution Units have been used worldwide in Lead Acid Battery plants and Acid Distribution companies.

A full installation and training service is provided with each unit.

Model	Dilution Capacity (m ³ /hr)	Diameter (m)	Height (m)	Cooling Requirement
4:4	1	2	2.5	88
2:1	2	1.2	2	176
4:2	2	2	2.5	176
5:2	2.5	2	3	218
6:2	3	2	3	262
8:2	4	2.5	2.5	349
10:2	5	2.5	3	435
2.5:0.5	5	N/A		533

CHEM RESIST

Britannia House, Lockway, Ravensthorpe Industrial Estate, Dewsbury,
West Yorkshire, UK, WF13 3SX

Tel: +44(0)1924 499 466 Fax: +44(0)1924 490 334

www.chemresist.com
info@chemresist.com